



# DecTec<sup>®</sup> PRODUCT PROFILE



## THE PRODUCT ADVANTAGE

DecPatchII offers the best in filler capabilities combined with on site workability and ease of mixing. Use DecPatchII to fill plywood joints and imperfections in the substrate such as voids and knots. The patch is a strong, cementitious material which once sanded, results in a smooth substrate contributing to a beautiful finished appearance.

For additional information or MSDS sheets, please contact Skyline, toll-free at 1-866-461-3914 or [www.dec-tec.com](http://www.dec-tec.com).

## PRODUCT NAME: DecPatch II

### FEATURES:

- Grey odorless powder
- Easy on site preparation with water
- Bags make transportation easy and clean
- Compatible with all DecTec membranes and adhesives

### PACKAGING:

- 10 lb / 4.5 kg pail

### TECHNICAL NOTES:

- Application Temperature: 50 °F - 100 °F (10 °C - 38 °C)
- Application Thickness: Skim coat to 1/2" (12mm)
- Apply only over completed dry substrates
- Working Time: 15 minutes
- Allow 12 hours to cure

### NOTES:

This document is not an installation guideline. Applicators must fully read, and understand, our Installation Manual before using or installing any of our products. Skyline will not be responsible for improper use or installation of our products.